
Ordering Information

 $Suffix the \, material \, designator \, to \, the \, part \, number. \,\, Example: \, DU-8-S$


Table 18. Material Designator

Material	Designator
Stainless Steel316	S
Dual Grade	3
Brass	В
Carbon Steel	С
Stainless 310	310
Duplex	D
Super Duplex	SD
Aluminum	AL
Alloy 20	L20
Hastelloy C276	HC
Alloy 400	M
Alloy 600	IN
Alloy 625	L625
Alloy 825	L825
Titanium Gr. 2	TI
PTFE	PE

Tee and Cross Fittings



Tee fitting part number is described by first the run (1 and 2) and next the branch (3).



Cross fitting part number is described by first the run (1 and 2) and next the branch (3 and 4)

Table 19. Pipe Thread Size Designator

Nom. Size in.	1/16	1/8	1/4	3/8	1/2	3/4	1	1-1/4	1-1/2	2
Designator	1	2	4	6	8	12	16	20	24	32





Material

 $\label{lem:decomposition} DK-Lok\,Z\,Series\,single\,ferrule\,tube\,fitting\,is\,designed\,and\,manufactured\,to\,the\,highest\,quality\,standards.$

This fitting includes single ferrule with standard DK-Lok fitting body and nut.

To help identify DK-Lok Z series from DK-Lok Tube fitting, nut is black Molybdenum Disulfide (MoS2) coated

OD in.	1/16	1/8	3/16	1/4	5/16	3/8	1/2	5/8	3/4	7/8	1	11/4	1 1/2	2		
Designator	1	2	3	4	5	6	8	10	12	14	16	20	24	32		
OD mm	2mm	3 mm	4 mm	6 mm	8mm	10 mm	12 mm	16 mm	20 mm	22 mm	25 mm	28 mm	32 mm	38 mm	42 mm	50 mm
Designator	2M	3 M	4 M	6 M	8 M	10 M	12 M	16 M	20 M	22 M	25 M	28 M	32 M	38 M	42 M	50 M

Table 20. Tube O.D. Designator

Z series DK-Lok

DK-Lok Z Series single ferrule tube fitting is manufactured in stainless steel 316.

Pressure and Temperature Ratings

DK-Lok Z Series fittings are identical to DK-Lok Tube Fittings in pressure and temperature ratings.

Dimensions

 $\operatorname{DK-Lok} Z$ Series fittings are dimensionally identical to $\operatorname{DK-Lok} Tube$ Fittings.

Ordering Information

To order Z series, insert Z in the standard DK-Lok tube fitting part number

Examples: DUZ-8-S, DMCZ8-8N-S, DNZ-4-